

CARRASQUILLO ASSOCIATES, LTD.

**MATERIALS, CONSTRUCTION, AND
STRUCTURAL CONSULTANTS**

TBPE Reg. F-3467

5113 SOUTHWEST PARKWAY, STE. 250
AUSTIN, TX 78735

October 16, 2018

Mr. Manuel Mata
Director de Complejo
AES Puerto Rico, L.P.
PO Box 1890
Guayama, PR 00785

**RE: Investigation into the existing Agremax Storage Pile at AES-PR
Title 40: Protection of the Environment: Part 257 – Criteria
for Classification of Solid Waste Disposal and Practices**

Dear Mr. Mata:

Presented herein are the results of Carrasquillo Associates' (CA) investigation into determining if the Agremax Storage Pile at the AES – PR Power Plant located in Guayama, PR, meets the requirements in the regulation in Title 40: Protection of the Environment, Part 257 – Criteria for Classification of Solid Waste Disposal and Practices. Review of the regulation revealed that the applicable section of the Part 257 – Criteria for Classification of Solid Waste Disposal and Practices regulation applicable to the Agremax Storage Pile at AES-PR is Subpart D-Standard for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments, §257.64, Unstable Areas.

The investigation included, among others, a detailed analysis of the applicable regulations, detailed inspection of the Agremax Storage Pile, geotechnical sampling, testing and analysis of the landfilled material and subsurface soil, topographical evaluation, and an engineering assessment of the geotechnical characteristics of the site. As stated in §257.64, Unstable Areas, the following factors were addressed in the investigation into the adequacy of the Agremax Storage Pile at AES-PR.

These include:

- On-Site or local soil conditions that may result in significant differential settling,
- On-site or local geological or geomorphologic features,
- On-site or local human-made features or events (both surface and subsurface), and
- Slope stability and mass movements.

The geotechnical laboratory testing program included the following:


- Soil Classification,
- Consolidation Tests,
- Triaxial Tests,
- Direct Shear Testing, and
- Modified Proctor Compaction Testing.

Details of the geotechnical investigation conducted are included in the report from Mr. Carlos R. Sierra Del Llano, MSCE, PE, with Jaca & Sierra Testing Laboratories dated October 15, 2018, titled ON THE GEOTECHNICAL EXPLORATION CONDUCTED AT THE SITE OF THE EXISTING AGREMAX STORAGE PILE AT AES FACILITIES, GUAYAMA, PR. (Copy attached)

The results of the investigation reported herein indicate that the Agremax Storage Pile at the AES-PR Facilities in Guayama, PR, meets the requirements in the regulation Part 257 "Criteria for Classification of Solid Waste Disposal and Practices", Subpart D "Standard for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments" of the code of Federal Regulations, also known as CFR Rule.

If you have any questions regarding this letter, please do not hesitate to contact CA at 512-358-7020.

Submitted by:



Ramón L. Carrasquillo, Ph.D., P.E.
President, Carrasquillo Associates, LTD

W/attachments

CERTIFICATION

The results of the investigation reported herein indicate that the Agremax Storage Pile at AES-PR meets the requirements of 40 CFR 257.64 (a). I certify that this document was prepared by me or under my supervision or direction and that I am a professional engineer under the laws of Puerto Rico.

Date: October 16, 2018





REPORT

**ON THE GEOTECHNICAL EXPLORATION
CONDUCTED AT THE SITE OF THE EXISTING
AGREMAX STORAGE PILE,
AES FACILITIES
GUAYAMA, PR**

Submitted to:

Ramon Carrasquillo, PhD

Carrasquillo and Associates

Prepared by:

Carlos R. Sierra Del Llano MSCE, PE

Date:

October 15, 2018

Job No. 7899 Rev A



Table of Contents:

<u>1.0 INTRODUCTION:</u>	<u>2</u>
<u>2.0 SCOPE OF WORK:</u>	<u>3</u>
2.1 Geotechnical Drilling:	3
2.2 Laboratory Testing:	3
<u>3.0 Geotechnical Evaluation:</u>	<u>4</u>
3.1 Unstable Areas:	4
3.1.1 Total and Differential Settlements:	5
3.1.2 Geologic and Geomorphologic Features:	7
3.1.3 Human-made Features or events:	9
3.1.4 Slope Stability:	9
<u>4.0 CONCLUSION:</u>	<u>11</u>
<u>5.0 ADDITIONAL COMMENTS:</u>	<u>11</u>
<u>REFERENCES</u>	<u>12</u>



GEOTECHNICAL REPORT

ON THE EXPLORATION PERFORMED AT THE SITE OF THE AGREMAX STORAGE PILE AT AES FACILITIES, GUAYAMA, PR

1.0 INTRODUCTION:

Jaca & Sierra Engineering, PSC was contracted by *Carrasquillo Engineering Services Group* to perform site investigations in order to address the “Standards for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments” as specified in Subpart D of the “Criteria for Classification of Solid Waste Disposal Facilities and Practices” of the Code of Federal Regulation, which is part of the federal regulations known as the CFR Rule.

The exploration program was directed to obtain subsurface soil information to evaluate unstable areas as specified in sections 257.64 of these Code of Regulations.

This geotechnical report has been prepared for the exclusive use of the owner, their architects, engineers and others involved in the evaluation of the “Criteria for Classification of Solid Waste Disposal Facilities and Practices”.



2.0 SCOPE OF WORK:

2.1 Geotechnical Drilling:

The field exploration consisted of drilling *five* (5) borings located along the perimeter and within the Agremax storage pile. The borings were drilled to a depth of 25 to 60 ft below existing ground surface (B.E.G.S.). Boring locations are shown on Appendix A and Boring logs on Appendix B of this report.

In situ testing and soil sampling was achieved by means of the universally adopted Standard Penetration Test (SPT) and split spoon sampler method according to ASTM D 1586. Subsurface drilling was executed by means of the power auger method as per ASTM D 1452 using a CME-55 drill rig to drive a 2.25 inches I.D. helical auger into the ground.

Collected soil samples throughout the investigation were delivered to our laboratory to perform analyses of moisture content, unconfined compressive strength, and soil classifications. The data collected was eventually used to formulate the engineering recommendations provided in this report.

2.2 Laboratory Testing:

The following laboratory tests were performed to evaluate the requirements of sections 257.62 through 257.64 of the Code of Regulations:

- Consolidation tests (3);



- Triaxial test on remolded Aggremax sample (1);
- Direct Shear test (3);
- Modified Proctor Compaction test (3);
- and Soil Classifications (3).

3.0 Geotechnical Evaluation:

Per contracted scope of work, this geotechnical investigation is intended and limited to address section 257.64 of Subpart D of the “Criteria for Classification of Solid Waste Disposal Facilities and Practices” of the Code of Federal Regulations. This section states the following:

“An existing or new CCR landfill, existing or new CCR surface impoundment, or any lateral expansion of a CCR unit must not be located in an unstable area unless the owner or operator demonstrates...that recognized and generally accepted good engineering practices have been incorporated into the design of the CCR unit to ensure that the integrity of the structural components of the CCR unit will not be disrupted.”

Based on the above requirement, our evaluation is limited to the definition of unstable areas for the existing Agremax Storage Pile.

3.1 Unstable Areas:

The CFR rule definition of unstable area on section 257.53 is quoted as follows:

“Unstable area means a location that is susceptible to natural or human-induced events or forces capable of impairing the integrity, including structural components of some or all of the



CCR unit that are responsible for preventing releases from such unit. Unstable areas can include poor foundation conditions, areas susceptible to mass movements, and karst terrains”

The term poor foundation conditions is defined as follows:

“Poor foundation conditions mean those areas where features exist which indicate that a natural or human-induced event may result in inadequate foundation support for the structural components of an existing or new CCR unit. For example, failure to maintain static and seismic factors of safety as required in §§257.73(e) and 257.74(e) would cause a poor foundation condition.”

Based on the above definitions, our report will address the following:

- On-site or local soil conditions that may result in significant differential settling;
- On-site or local geologic or geomorphologic features;
- On-site or local human-made features or events (both surface and subsurface).
- Slope stability and mass movements.

3.1.1 Total and Differential Settlements:

Three (3) exploratory borings were performed along the perimeter of the Agremax storage pile to uncover the subsurface soil stratigraphy beneath the unit. The borings revealed a medium-to-stiff fill layer composed of a mixture of Agremax and clayey soils



that extends to approximately 15 ft beneath existing ground surface. The fill layer is followed by a soft to medium clayey layer described as silty clay with some sand that extends to about 24 ft before transitioning to a medium-to-stiff clay.

A total of three (3) shelby tube undisturbed soil samples were retrieved from the clayey layer to perform tests that assisted in determining the magnitude of consolidation of the compressible soils. The undisturbed samples were obtained from Boring no.2 at 20-22 ft and from Boring no.3 at 14-16 ft and 24-26 ft.

Consolidation tests were performed on the undisturbed soil samples following ASTM D2435. To evaluate the differential settlement within the footprint area of the Agremax storage pile, the magnitude of settlement at the center of the deposit was compared to the magnitude of settlement at a corners. To consider the most critical scenario, the center of the area was assumed to have a soil profile similar to boring no.3 where soft to medium clay soils extend to about 49 ft, while the soil profile at the corner was assumed to be similar to Boring no.1 where the compressible soils extend to about 24 ft beneath existing ground surface.

With these assumptions the magnitude of total settlement at the center of the Agremax storage pile resulted in approximately 14 inches and the magnitude of settlement at the corner of the structure resulted in 5 inches, for a differential settlement of 9 inches. Considering a distance of 300 ft measured from the center of the storage pile



towards Boring no.1, a differential settlement of 9 inches results in an angular distortion of approximately 0.14 degrees (1:400). This magnitude of angular distortion can be considered as tolerable for this particular structure, over such the significant distance of 300 ft. Based on our observations during the site visit, there are no signs of significant displacements or cracks on the area of the stockpile.

In consideration of the above described analysis and observations it is our opinion that the facility is in compliance with 257.64 section for existing structures in what relates to settlement.

3.1.2 Geologic and Geomorphologic Features:

The site's near surface geology is mainly "Qf" deposit, which corresponds to alluvial fans. This alluvial deposit was encountered at about 14 ft below existing ground surface and continued throughout the final drilled depth of 60 ft. The deposit was mainly described as clayey silt with some sand and varied between soft to stiff consistency. A detailed description of the geological formation on site is included below, along with an illustration of the USGS geological map for the Central Aguirre quadrangle¹.

¹ Henry L. Berryhill, Jr. (1960) Geology Map of Central Aguirre, PR-Map I 318, U.S. Geological Survey, U.S. Department of Interior, Washington, D.C.



Figure 1: USGS Geology Map - Central Aguirre Quadrangle

- **Qf: (Alluvial fans)** – “Unconsolidated stratified clay, silt, sand, gravel, cobbles and boulders; cobbles and boulders mainly in the northern part of alluvial fans; clay, silt, and sand are predominant components of southern half to one-third of fans; areas high in salt, Qfs.”

This site does not have karst related geology or karst features as defined in the CFR rule. Also there are no existing geologic hazards such as landslide zones prone to mass movements or rock fall. The sites near surface geologic features, as described above, do not represent an unstable condition for the Agremax Storage Pile’s perimeter.

3.1.3 Human-made Features or events:

Between the dates of site reconnaissance (September 6th, 2018) and conclusion of field work (September 11th, 2018) no human-made features could be identified on site that could represent an unstable condition or that possess a threat to the stability of the structure.

3.1.4 Slope Stability

The applicable CFR Rule for slope stability verification for the Agremax Storage pile is 257.73(e)- Structural integrity criteria for existing CCR surface impoundments; which requires the following:

“(e) Periodic safety factor assessments. (1) The owner or operator must conduct an initial and periodic safety factor assessments for each CCR unit and document whether the calculated factors of safety for each CCR unit achieve the minimum safety factors specified in paragraphs (e)(1)(i) through (iv) of this section for the critical cross section of the embankment. The critical cross section is the cross section anticipated to be the most susceptible of all cross sections to structural failure based on appropriate engineering considerations, including loading conditions...”

“(i) The calculated static factor of safety under the long-term, maximum storage pool loading condition must equal or exceed 1.50.

(ii) The calculated static factor of safety under the maximum surcharge pool loading condition must equal or exceed 1.40.

(iii) The calculated seismic factor of safety must equal or exceed 1.00.”

Slope stability was modeled with Slope w software for various critical profiles taken from the existing topography drawings prepared by Agrim. Julio C. Soto CSP, per

drawings dated Sept. 17, 2018, which are enclosed in this report. Data from the field and laboratory tests was incorporated into the model. In consideration of the cohesion that develops from cementing of particles that occurs from the Agremax installation process, the high friction angles and relatively light weight nature of the CCR material (max density ranging from 70 to 80 pcf), the slopes were found to have a Factor of Safety (FS) of over 1.5 for static condition and 1.1 for seismic. These FS values exceed requirements of CFR rule 257.73(e) and standard of practice for geotechnical engineering.




Figure 2: Static condition slope stability analysis.



4.0 CONCLUSION:

Based on the herein presented findings and the requirements of section 257.64, it is our professional opinion that the existing Agremax Storage Pile is in compliance with the location restriction requirements of unstable areas, as described in 40 CFR subsections 257.64(a) and 257.64(b).

5.0 ADDITIONAL COMMENTS:

This report is based on our evaluation of the site conditions at the time of the engineer visits, field investigations and information made available to us at the time this report was prepared.

The herein given recommendations are based on test borings performed on spots, which are considered as representative of the subsoil conditions within the project site. It is our opinion that these investigation, laboratory testing and engineering assessment has been made in accordance to geotechnical standards of practice.

We wish to thank you for the opportunity of preparing this geotechnical engineering report.

Respectfully submitted,
JACA & SIERRA ENGINEERING, PSC.

A handwritten signature in blue ink, appearing to read "Carlos R. Sierra Del Llano".

Carlos R. Sierra Del Llano, MSCE, PE

Enclosures

REFERENCES

Henry L. Berryhill, Jr. (1960) Geology Map of Central Aguirre, PR-Map I 318, U.S. Geological Survey, U.S. Department of Interior, Washington, D.C.

CERTIFICATION

The demonstration herein meets the requirements of 40 CFR 257.64 (a). I certify that this document was prepared by me or under my supervision and that I am a registered professional engineer under the laws of Puerto Rico.

Certified by: Carlos R. Sierra Del Llano, MSCE, PE


Date: 10-15-18



Appendix A:

Boring Locations Plan

Drawing Name: C:\A PROYECTOS ACTUALES 3-22-18\JesTrab.2018\JCS1836F.dwg Last Modified: Sep 17, 2018 - 8:23am by User



PLANO DE LOCALIZACIÓN

ESCALA = 1 : 20,000

NOTAS :

- 1 - LOS CONTROLES HORIZONTALES USADOS EN ESTE MAPA ESTÁN REFERIDOS A NAD83 (NA2011) EPOCH 2010.
- 2 - TODAS LAS DISTANCIAS ESTAN EN METRO A MENOS QUE SE INDIQUE LO CONTRARIO.
- 3 - EL TRABAJO FUE REALIZADO CON 4 UNIDADES TRIMBLE CON TECNOLOGÍA GPS.
- 4 - EL CONTROL VERTICAL ESTÁ REFERIDO A UN NIVEL ARBITRARIO PARA EL PROYECTO, NO ESTÁ REFERIDO A NINGÚN SISTEMA PREVIAMENTE ESTABLECIDO.

LEYENDA :

- 5 --- CONTORNO DE NIVEL A 1.00 METRO
- CONTORNOS DE NIVEL A 0.50 METRO
- B2 --- "BORING"
- CAMINO EN TIERRA
- MURO PEQUEÑO
- 4.75 --- ELEVACIONES

CERTIFICACIÓN

JULIO C. SOTO SERRANO
Agrimensor Licencia num. 9633

Dib. Cadd por: JOA
Fecha : 17 DE SEPT. DE 2018
Escala : 1:500
Proy. Num. : JCS1836F
Hoja Num. : 1 de 1


PLANO TOPOGRÁFICO DE DEPOSITO DE MATERIAL EN LAS FACILIDADES DE AES PUERTO RICO, LP

BARRIO JOBOS, GUAYAMA, PUERTO RICO

Agrim. Julio C. Soto Serrano, CSP
JCS
Servicios de Agrimensura
Agrimensor Lic. 9633
Avenida Emérito Estrada Rivera Num.1490
San Sebastián, Puerto Rico
TEL: (787) 280-0565 • Fax: (787) 280-3333
E-mail: agrimpc@gmail.com
PO Box 1592
San Sebastián
Puerto Rico 00685

Appendix B:

Boring Logs



SUBSURFACE EXPLORATION LOG

BORING No.: 1

PROJECT: AES **JOB:** 7899 **SHEET OF** 1 2

LOCATION: Guayama, PR **DRILLER/DRILL RIG:** Carlos I. Diaz / CME-55

COORDINATES: **DATE STARTED:** 9-10-18 **DATE COMPLETED:** 9-10-18


DESCRIPTION BY: Manuel Candelario **SURFACE ELEVATION (ft):**

GROUNDWATER (ft): Initial: 4 Final: 3.5 **ENGINEER:** Manuel Candelario

DRILLING METHOD: Hollow-Stem Auger 2.25" ID **TOTAL DEPTH (ft):** 50.5

DRILLING METHOD: Hollow-Stem Auger 2.25" ID												17-2015						
ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	○ N □ W △ Qu						
												Qu	1	2	3	4		
												N-W	20	40	60	80		
0.00	0	FILL: clayey silt with sand some gravel, medium to stiff, yellowish brown		S-1		4 6 7	13	13										
				S-2		6 6 6	12	11										
				S-3		4 4 4	8	17										
	5																	
-6.00	6	FILL: gravel some clayey sand, dense, grayish brown		S-4		18 21 22	43	12										
-10.00	10	SILTY CLAY some sand, medium to stiff, grayish brown		S-5		10 8 7	15	23										
				S-6		3 4 5	9	25	1.2									
-14.00	14	SANDY CLAY, very soft, grayish brown		S-7		WH WH WH	WH	26										
	15																	
	20			S-8		WH WH 1	1	27										
-24.00	24	SILTY CLAY some sand, medium to stiff, yellowish brown, reddish brown		S-9		WH 3 3	6	24	1.0									
	25																	
	30			S-10		5 10 11	21	18	3.2									
				S-11		3	12	23	0.8									

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
 "W" - Natural Moisture Content in percentage of dry weight.
 "Qu" - Unconfined Compressive Strength in tons per square foot.
 "Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
 "WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
 "P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING NUMBER: 1

BORING LOG (CONT. SHEET)

PROJECT

JOB

7899

SHEET

2

OF

2

												C				
												○ N	□ W	△ Qu		
ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	Qu	1	2	3	4
	0.00											N-W	20	40	60	80
	35					5 7										
-39.00																
	40	CLAYEY SAND with gravel, loose to medium, very stiff, reddish brown, reddish yellow		S-12		3 6 6	12	27								
	45			S-13		3 3 4	7	21								
-49.00																
	50	SILTY CLAY some sand trace gravel, very stiff, reddish brown, reddish yellow		S-14		6 11 16	27	19	2.3							
	55															
	60															
	65															
	70															

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.

"W" - Natural Moisture Content in percentage of dry weight.

"Qu" - Unconfined Compressive Strength in tons per square foot.

"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.

"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.

"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



BORING No.: 2

SHEET	1
OF	1


DRILLER/DRILL RIG:	Carlos I. Diaz / CME-55
---------------------------	-------------------------


DATE COMPLETED: 9-8-18

SURFACE ELEVATION (ft):

ENGINEER: Manuel Candelario

TOTAL DEPTH (ft):	25.5
--------------------------	------

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
 "W" - Natural Moisture Content in percentage of dry weight.
 "Qu" - Unconfined Compressive Strength in tons per square foot.  Initial G.W. Depth
 "Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
 "WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
 "P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING No.: 3

PROJECT: AES **JOB:** 7899 **SHEET** 1
OF 2

LOCATION: Guayama, PR **DRILLER/DRILL RIG:** Carlos I. Diaz / CME-55

COORDINATES: **DATE STARTED:** 9-7-18 **DATE COMPLETED:** 9-7-18

DESCRIPTION BY: Manuel Candelario **SURFACE ELEVATION (ft):**

GROUNDWATER (ft): Initial: 7.5 Final: **ENGINEER:** Manuel Candelario

DRILLING METHOD: Hollow-Stem Auger 2.25" ID **TOTAL DEPTH (ft):** 60.5

ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	<div>○ N □ W △ Qu</div> <div>Qu 1 2 3 4</div> <div>N-W 20 40 60 80</div>			
0.00	0	FILL: clayey silt with sand trace gravel, stiff to very stiff, grayish brown		S-1		4	12	76							
				S-2		6									
						6									
				S-3		10	27	30							
						11									
						16									
-4.00	5	Aggremax		S-4		9	50	50							
						50									
				S-5		23	27	65							
						16									
						11									
	10			S-6		12	50/2"	19							
						50/2"									
-14.00	15	SILTY CLAY some sand, medium, grayish brown		S-7		3	6	21	0.6						
						3									
						3									
-19.00	20	SAND some silt trace gravel, medium, gray		S-8		4	14	22							
						6									
						8									
				S-9		2	4	37	1.2						
						2									
						2									
-24.00	25	SILTY CLAY some sand, soft to medium, brownish gray		S-10		2	6	19							
						2									
						4									
	30														
		Do... stiff, yellowish brown													
				S-10		3	14	18							

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.


"W" - Natural Moisture Content in percentage of dry weight.

"Qu" - Unconfined Compressive Strength in tons per square foot.

"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.

"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.

"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING NUMBER: 3

BORING LOG (CONT. SHEET)

PROJECT

AES

JOB

7899

SHEET


2

OF

2

ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	Qu												
												○ N	□ W	△ Qu										
												Qu	1	2	3	4								
	0.00											N-W	20	40	60	80								
	35	Do... some sand, soft to medium, yellowishbrown, reddish brown		S-11		6 8	8	20	0.8															
						3 3 5																		
	40																							
	45																							
						S-12												WH 2 2	4	26				
	50	Do... stiff to hard yellowish brown		S-13		6 7 14	21	19	3.8															
	55			S-14		3 3 6	9	21	0.7															
	60			S-15		22 28 29	57	13	0.8															
	65																							
	70																							

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
"W" - Natural Moisture Content in percentage of dry weight.
"Qu" - Unconfined Compressive Strength in tons per square foot.
"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING No.: 4

PROJECT: AES **JOB:** 7899 **SHEET** 1
OF 2

LOCATION: Guayama, PR **DRILLER/DRILL RIG:** Carlos I. Diaz / CME-55

COORDINATES: **DATE STARTED:** 9-11-18 **DATE COMPLETED:** 9-11-18


DESCRIPTION BY: Manuel Candelario **SURFACE ELEVATION (ft):**

GROUNDWATER (ft): Initial: Not Found Final: **ENGINEER:** Manuel Candelario

DRILLING METHOD: Hollow-Stem Auger 2.25" ID **TOTAL DEPTH (ft):** 50.5

DRILLING METHOD: Hollow-Stem Auger 2.25" ID												17-5615				
ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	○ N □ W △ Qu				
	0.00											Qu	1	2	3	4
0.00	0	Aggremax		S-1		3 5 4	9	70				N-W	20	40	60	80
				S-2		3 4 8	12	53								
	5			S-3		7 25 40/2"	40/2"	40								
				S-4		9 14 9	23	40								
	10			S-5		34 40/1"	40/1"	26								
				S-6		22 16 40/4"	40/4"	60	1.9							
	15			S-7		4 8 15	23	78								
	20			S-8		5 8 13	21	77								
	25			S-9		28 40/2"	40/2"	47								
	30			S-10		7	31	62								

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
 "W" - Natural Moisture Content in percentage of dry weight.
 "Qu" - Unconfined Compressive Strength in tons per square foot.
 "Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
 "WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
 "P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING NUMBER: 4

BORING LOG (CONT. SHEET)

PROJECT

JOB

7899

SHEET


2

OF

2

												AES										
ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	AES										
												Qu										
												N	W	Qu								
	0.00											Qu	1	2	3	4						
												N-W	20	40	60	80						
	35			S-11		12 19	39	59														
						8 16 23																
	40					S-12								4 4 13	17	95						
	45																					
						S-13								7 27 40/2"	40/2"	62						
	50																					
55																						
60																						
65																						
70																						

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
"W" - Natural Moisture Content in percentage of dry weight.
"Qu" - Unconfined Compressive Strength in tons per square foot.
"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING No.: 5

PROJECT: AES **JOB:** 7899 **SHEET** 1
OF 2

LOCATION: Guayama, PR **DRILLER/DRILL RIG:** Carlos I. Diaz / CME-55

COORDINATES: **DATE STARTED:** 9-11-18 **DATE COMPLETED:** 9-11-18


DESCRIPTION BY: Manuel Candelario **SURFACE ELEVATION (ft):**

GROUNDWATER (ft): Initial: Not Found Final: **ENGINEER:** Manuel Candelario

DRILLING METHOD: Hollow-Stem Auger 2.25" ID **TOTAL DEPTH (ft):** 50.5

ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	○ N □ W △ Qu				
												Qu	1	2	3	4
0.00	0	Aggremax		S-1	8 42 45		87	45					20	40	60	80
				S-2	40/3"	40/3"	28									
	5			S-3	3 3 4		7	45								
				S-4	40/5"	40/5"	25									
	10			S-5	33 40/2"	40/2"	35									
	15			S-6	8 12 21		33	59								
	20			S-7	5 7 20		27	53								
	25			S-8	6 12 37		49	48								
	30			S-9	16 16 15		31	53								
				S-10	12		29	68								

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
"W" - Natural Moisture Content in percentage of dry weight.
"Qu" - Unconfined Compressive Strength in tons per square foot.
"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.



SUBSURFACE EXPLORATION LOG

BORING NUMBER: 5

BORING LOG (CONT. SHEET)

PROJECT

JOB








7899

SHEET

2

OF

2


												CORRELATION									
ELEV (ft)	DEPTH (ft)	DESCRIPTION	LEGEND	SAMPLE NO.	TYPE	BLOWS	SPT N	W	Qu	RC	RQD%	CORRELATION									
												Qu	1	2	3	4					
	0.00											N-W	20	40	60	80					
	35					15 14	32	58													
	40												S-11		8 13 19						
	45												S-12		5 7 12	19	59				
	50												S-13		6 8 12	20	58				
																					
	55																				
	60																				
	65																				
70																					

"N" - Number of blows required to drive the sampling spoon a distance of 12 in. with a 140 lbs hammer falling 30 in.
"W" - Natural Moisture Content in percentage of dry weight.
"Qu" - Unconfined Compressive Strength in tons per square foot.
"Rc" - Core recovery in percent for each successive run. "RQD" - Rock quality designation.
"WH" - Sample was recovered by advancing the sampler with the weight of the hammer.
"P" - A "P" in the Unconfined Compressive Strength test indicates the use of the pocket Penetrometer.

Appendix C:

Laboratory Test Results

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	0.0	38.3	61.7	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#4	100.0		
#10	100.0		
#40	88.0		
#100	69.3		
#200	61.7		

* (no specification provided)

Material Description

Sandy silt.
Aggremax Grab

Atterberg Limits

PL= NP LL= NP PI= NP

Coefficients

D₈₅= 0.355 D₆₀= D₅₀=
D₃₀= D₁₅= D₁₀=
C_u= C_c=

Classification

USCS= ML AASHTO= A-4(0)

Remarks

Tested by: L. Medina
Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 1 Source of Sample: Project Site
Location: Guayama, PR Source Sample: Project Site

Date: 9/10/18
Elev./Depth:


JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure

COMPACTION TEST REPORT




Test specification: ASTM D 1557-00 Method C Modified

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/4 in.	% < No.200
	USCS	AASHTO						
	ML	A-4(0)			NP	NP	0.0	61.7

TEST RESULTS		MATERIAL DESCRIPTION	
Maximum dry density = 76.0 pcf Optimum moisture = 38.4 %		Sandy silt. Aggremax Grab	
Project No. 7899 Client: Carrasquillo Engineering Services Project: CDR Landfill at AES, Guayama, PR Date: 9/7/18 ● Location: Guayama, PR Source Sample: Project Site		Remarks: Tested by: F. Santos Checked by: Rommel Cintron Aponte, MSCE, PE Job No.: 7899	
JACA & SIERRA TESTING LABORATORIES San Juan, Puerto Rico		Figure	

Figure

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	0.0	56.4	43.6	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#4	100.0		
#10	99.6		
#40	90.1		
#100	59.3		
#200	43.6		

* (no specification provided)

Material Description

Clayey sand.

Atterberg Limits

PL= 17 LL= 27 PI= 10

Coefficients

D₈₅= 0.362 D₆₀= 0.154 D₅₀= 0.101
D₃₀= D₁₅= D₁₀=
C_u= C_c=

Classification

USCS= SC AASHTO= A-4(1)

Remarks

Tested by: L. Medina
Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 2
Location: Guayama, PR

Source of Sample: Project Site

Date: 9/11/18
Elev./Depth: 20-22'


JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	3.9	35.3	60.8	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
.375 in.	100.0		
#4	96.1		
#10	92.3		
#40	82.5		
#100	70.1		
#200	60.8		

* (no specification provided)

Material Description

Sandy lean clay.

Atterberg Limits

PL= 16 LL= 32 PI= 16

Coefficients

D₈₅= 0.563 D₆₀= D₅₀=
D₃₀= D₁₅= D₁₀=
C_u= C_c=

Classification

USCS= CL AASHTO= A-6(7)

Remarks

Tested by: A. Perez
Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 3
Location: Guayama, PR

Source of Sample: Project Site

Date: 9/17/18
Elev./Depth: 14-16'


JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	0.0	3.2	96.8	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#4	100.0		
#10	100.0		
#40	99.2		
#100	97.6		
#200	96.8		

* (no specification provided)

Material Description

Fat clay.

Atterberg Limits

PL= 26

LL= 57

PI= 31

Coefficients

D₈₅=

D₆₀=

D₅₀=

D₃₀=

D₁₅=

D₁₀=

C_u=

C_c=

Classification

USCS= CH

AASHTO= A-7-6(35)

Remarks

Tested by: A. Perez

Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 3
Location: Guayama, PR

Source of Sample: Project Site

Date: 9/17/18
Elev./Depth: 24-26'


JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	0.0	46.1	53.9	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#4	100.0		
#10	99.7		
#40	80.8		
#100	62.0		
#200	53.9		

* (no specification provided)

Material Description

Sandy silt.
Aggremax Grab

Atterberg Limits

PL= NP LL= NP PI= NP

Coefficients

D₈₅= 0.553 D₆₀= 0.130 D₅₀=
D₃₀= D₁₅= D₁₀=
C_u= C_c=

Classification

USCS= ML AASHTO= A-4(0)

Remarks

Tested by: L. Medina
Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 4

Location: Guayama, PR

Source of Sample: Project Site

Source Sample: Project Site

Date: 9/10/18

Elev./Depth:


JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure

COMPACTION TEST REPORT




Test specification: ASTM D 1557-00 Method C Modified

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/4 in.	% < No.200
	USCS	AASHTO						
	ML	A-4(0)			NP	NP	0.0	53.9

TEST RESULTS		MATERIAL DESCRIPTION
Maximum dry density = 68.8 pcf Optimum moisture = 41.6 %		Sandy silt. Aggremax Grab
Project No. 7899 Client: Carrasquillo Engineering Services Project: CDR Landfill at AES, Guayama, PR Date: 9/7/18 ● Location: Guayama, PR Source Sample: Project Site		Remarks: Tested by: J. Ortiz/J. Cordova Checked by: Rommel Cintron Aponte, MSCE, PE Job No.: 7899
JACA & SIERRA TESTING LABORATORIES San Juan, Puerto Rico		Figure

Figure

COMPACTION TEST REPORT




Test specification: ASTM D 1557-00 Method C Modified

Elev/ Depth	Classification		Nat. Moist.	Sp.G.	LL	PI	% > 3/4 in.	% < No.200
	USCS	AASHTO						
	SM	A-4(0)			NP	NP	0.0	39.5

TEST RESULTS		MATERIAL DESCRIPTION	
Maximum dry density = 70.5 pcf Optimum moisture = 35.9 %		Silty sand. Aggremax Grab	
Project No. 7899 Client: Carrasquillo Engineering Services Project: CDR Landfill at AES, Guayama, PR Date: 9/7/18 ● Location: Guayama, PR Source Sample: Project Site		Remarks: Tested by: J. Ortiz/J. Cordova Checked by: Rommel Cintron Aponte, MSCE, PE Job. No. 7899	
JACA & SIERRA TESTING LABORATORIES San Juan, Puerto Rico		Figure	

Figure

Particle Size Distribution Report



% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY
0.0	0.0	60.5	39.5	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#4	100.0		
#10	99.6		
#40	64.1		
#100	47.9		
#200	39.5		

* (no specification provided)

Material Description

Silty sand.
Aggremax Grab

Atterberg Limits

PL= NP LL= NP PI= NP

Coefficients

D₈₅= 1.11 D₆₀= 0.339 D₅₀= 0.176
D₃₀= D₁₅= D₁₀=
C_u= C_c=

Classification

USCS= SM AASHTO= A-4(0)

Remarks

Tested by: L. Medina
Checked by: Manuel Candelario Cosme, MSCE, PE

Sample No.: Bo. 5
Location: Guayama, PR

Source of Sample: Project Site
Source Sample: Project Site

Date: 9/10/18
Elev./Depth:

JACA & SIERRA
TESTING LABORATORIES
San Juan, Puerto Rico

Client: Carrasquillo Engineering Services
Project: CDR Landfill at AES, Guayama, PR

Project No: 7899

Figure